

# DataSheet

With one of the widest ranges available on the market today, Commander® is firmly established as a true market leader. Time has proved these portable fire extinguishers as a dependable choice for almost any situation, and reliable performance is guaranteed.



## RENOVATED CO<sub>2</sub> EXTINGUISHERS

Our renovated CO<sub>2</sub> fire extinguishers are an extremely cost effective and economical solution for class B and electrical fires.

Old CO<sub>2</sub> fire extinguishers are shotblasted to remove all old paint and labels, new valve assemblies are then fitted, cylinders are refilled and then finally they are resprayed and labelled.

<b>Technical Specification</b>	2C/TFPV - SQUAT	5C/TFPV - SQUAT
Capacity	2kg	5kg
Fire Rating	34B	70B
Extinguishing Medium	CO <sub>2</sub>	CO <sub>2</sub>
Working Pressure	56 bar @ 20°C	56 bar @ 20°C
Temperature Range	-20-+60°C	-20-+60°C
Cylinder Material	Steel	Steel
Pressuring Gas	CO <sub>2</sub>	CO <sub>2</sub>

## **COMMANDER**®

2C/TFPV | 5C/TFPV

## PRODUCT GROUP

Commander® Extinguishers

## **DIMENSIONS (mm)** (height x width x diameter)

2C/TFPV: 515 x 185 x 220 5C/TFPV: 850 x 275 x 370

## **WEIGHT**

2C/TFPV: 5.04kg 5C/TFPV: 11.25kg

- Full range of spare parts available
- Corrosion-resistant finish
- 5-year warranty



029 2086 8333



029 2085 0627



sales@checkfire.co.uk



www.CheckFire.co.uk





