



TECHNICAL SPECIFICATION

Keepsafe Jaguar Safety Spectacles Code:292980

Conformity:

Conforms to BS EN 166.
EC Certificate Number 726, issued by
issued by Inspec Certification Limited.

Weights:

0.03Kg (Weight is approx.)

Materials:

Polycarbonate Arms and Lens

Markings:

Frame: EN166 1.F

Lens:	Clear – 2 – 1.2		1.F
	Amber – 2 – 1.2		1.F
	Smoke – 5 – 2.5		1.F
	Green – 2 – 3		1.F



Performance:

Lens and frame offer protection against low energy high-speed particles at 45 m/s (101 mph). The optical qualities of the lens comply with the requirements of optical class 1 (highest).

Instructions For Use:

In use ensure that the safety spectacles fit comfortably and securely on the head. Ensure that the safety spectacles are in place, before entering the hazard area.

Limitations Of Use:

Protection will only be offered if the safety spectacles are fitted correctly. If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately. Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer. The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eyeshield and seek medical advice. The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.

Notes:

- i. These safety spectacles are not suitable for protection against dusts, liquids or molten metals.*

Cleaning & Maintenance:

The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth. Do not clean with chemical or abrasive cleaners. The eyeshield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.