

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Line Marker Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Technical function Hand-held pre-pressurised aerosol

Application of the substance / the preparation: Line marking

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

One Stop Sourcing & Supply Co.
Homefield Road, Haverhill, Suffolk, CB9 8QP
United Kingdom
T: 01440 712060
E: sales@osssc.com

1.4 Emergency telephone number(s):

NHS Direct: 111

National Poisons Information Service (NPIS): 0121 507 4123 (healthcare professionals only).

Ireland - National Poisons Information Centre: 01 837 9964 or 01 809 2566 (healthcare professionals only).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms:



GHS02 GHS07

Signal word: Danger

Hazard-determining components of labelling:

acetone

Hazard statements:

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

Description: Mixture consisting of the following components.

Hazardous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether Flam. Gas 1, H220; Press. Gas (Comp.), H280	≥10-≤50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥20-≤25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥10-<20%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	Titanium dioxide Carc. 2, H351	≥2.5-≤10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≥2.5-≤10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation:

Move patient to fresh air, if symptoms persist consult a doctor.

Butane asphyxiation will precede any toxicological effects of the active elements.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Repeated contact may cause skin dryness and cracking.

After eye contact:

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Get medical attention.

NEVER PUT AEROSOLS NEAR EYES/MUCOUS MEMBRANES

After swallowing:

Call for a doctor immediately.

May cause nausea and discomfort. Perform gastric lavage to reduce discomfort.

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2

Dry powder

Sand

Earth

For larger fires, use foam, water fog or spray, avoiding contamination.

Use water only to cool undamaged broth.

5.2 Special hazards arising from the substance or mixture

Pressurized aerosols should not be exposed to temperatures above 50°C. Beyond this, containers may explode and the resulting flammable mixture will burn to produce CO2.

5.3 Advice for firefighters

Protective equipment:

Wear a positive pressure self-contained breathing apparatus

Wear fully protective suit.

Additional information: Avoid contamination of water where courses where damaged stock is leaking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Use personal protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

 Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up

In small quantities, any liquid should be absorbed in a suitable medium, such as sand, and disposed of safely. The residue should be washed off with soapy water, although staining is to be expected.

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

 Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

Information about storage in one common storage facility: Avoid contamination with other products.

Further information about storage conditions:

Keep container tightly closed.

Protect from heat and direct sunlight.

Protect from humidity and water.

Store in cool, dry conditions in well sealed receptacles.

Containers will not last indefinitely even when stored in a cool, dry place, they should be inspected periodically during long term storage.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL (Great Britain)	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
IOELV (EU)	Long-term value: 1920 mg/m ³ , 1000 ppm

67-64-1 acetone

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm

141-78-6 ethyl acetate

WEL (Great Britain)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
IOELV (EU)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
IOELV (EU)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Ensure good ventilation/exhaustion at the workplace.

Respiratory protection:

In case of brief exposure use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use organic/inorganic vapor filters. Vapors may cause drowsiness or dizziness.

Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

Due to missing tests no recommendation to the glove material can be given for the product/the preparation/the chemical mixture.

Select the glove material based on a consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time must be determined by the manufacturer of the protective gloves.

Eye/face protection



Safety glasses with side-shields (EN 166).

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Aerosol.
Colour:	Transparent.
Odour:	
Odour threshold:	Not determined.
Melting point/freezing point:	<-20 °C
Boiling point or initial boiling point and boiling range	>60 °C
Flammability	Not determined.
Lower and upper explosion limit	
Lower:	2.6 Vol % (67-64-1 acetone)
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Flash point:	0 °C
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
VOC (EC):	
Dynamic:	Not determined.
Solubility	
Water:	Insoluble.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density at 20 °C	0.94 kg/m ³
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
Solids content:	10-17 %

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

Softening point/range

Oxidising properties

Not determined.

Evaporation rate

Not applicable.

Information with regard to physical hazard classes

Explosives

Not applicable.

Flammable gases

Not applicable.

Aerosols

Extremely flammable aerosol. Pressurised container:
May burst if heated.

Oxidising gases

Not applicable.

Gases under pressure

Not applicable.

Flammable liquids

Not applicable.

Flammable solids

Not applicable.

Self-reactive substances and mixtures

Not applicable.

Pyrophoric liquids

Not applicable.

Pyrophoric solids

Not applicable.

Self-heating substances and mixtures

Not applicable.

Substances and mixtures, which emit flammable

gases in contact with water

Not applicable.

Oxidising liquids

Not applicable.

Oxidising solids

Not applicable.

Organic peroxides

Not applicable.

Corrosive to metals

Not applicable.

Desensitised explosives

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

The container is inherently stable under the prescribed conditions for a reasonable period of time (at least 24-25 months).

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Container corrosion can occur over time and damaged containers should be disposed of before a hazard arises.

10.4 Conditions to avoid

Keep away from sources of ignition.

Avoid high temperatures.

Avoid contact with acids

Protect against moisture.

Keep away from humidity and acids

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products No further relevant information available.

Additional information: Avoid sudden shocks, which can damage the integrity of the container.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

LD/LC50 values:

115-10-6 dimethyl ether

Inhalative	LC50/4h	308 mg/L (Rat)
------------	---------	----------------

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

67-64-1 acetone		
Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	20,000 mg/kg (Rabbit)
141-78-6 ethyl acetate		
Oral	LD50	5,620 mg/kg (Rabbit)
Inhalative	LC50/4h	1,600 mg/L (Rat)
13463-67-7 Titanium dioxide		
Oral	LD50	>20,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (Rabbit)
Inhalative	LC50/4h	>6.82 mg/L (Rat)
123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rabbit)
Inhalative	LC50/4h	>21 mg/L (Rat)

Serious eye damage/irritation: Causes serious eye irritation.**STOT-single exposure:** May cause drowsiness or dizziness.**11.2 Information on other hazards****11.2.1 Endocrine disrupting properties**

None of the ingredients are listed.

11.2.2 Other information

Deliberate inhalation may cause severe pulmonary and breathing difficulty, dizziness, drowsiness (narcosis) and headaches. This will constitute abuse.

Skin and eye irritation may result from continued exposure to vapors when used in areas of poor ventilation, or when working in close proximity to the spray for prolonged periods, and suitable steps should be taken to avoid such conditions.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****115-10-6 dimethyl ether**

LC50 13,000 mg/L (Fish)

NOEC/48h >4,000 mg/L (Fish)

12.2 Persistence and degradability

The degradation will be relatively slow but eventually almost complete.

12.3 Bioaccumulative potential Accumulation is unlikely once physical failure begins.**12.4 Mobility in soil** Mobility will be very slow.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional environmental information:**

Short and long term effects should not be considered significant. Very short term damage to aquatic and soil organisms may occur with a large spill (over 1000 containers), although this should disperse quickly (especially if absorbent material is used).

The product will evaporate quickly in the air. A colored liquid, easily absorbed, will evaporate and leave a solid. The solid will present no other significant hazard, with no hazard resulting from degradation.

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): Slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation:

Disposal must be made in accordance with official regulations.
Do not allow product to reach sewage system.
Do not puncture or incinerate/burn even after use.

Uncleaned packaging:

Recommendation:

Disposal must be made in accordance with official regulations.
Packaging that may not be cleansed must be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1 Gases.
Label 2.1

14.4 Packing group

ADR, IMDG, IATA Not applicable.

14.5 Environmental hazards

Not applicable.

14.6 Special precautions for user

Warning: Gases.

Hazard identification number (Kemler code): -

EMS Number: F-D,S-U

Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from"

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Tunnel restriction code:

D

IMDG

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients are listed.

Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms:

WEL: Workplace Exposure Limits

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Safety data sheet

according to 1907/2006/EC, Article 31, as amended by UK
REACH Regulation SI 2019/758

Printing date 28.09.2022

Version number 1

Revision: 28.09.2022

Trade name: Line Marker Spray

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3