

STYLE REF: PM4004

Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | SIZE UK 3-16 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, PLAIN FRONT GIBSON SHOE, ACTIV-STEP DUAL DENSITY OUTSOLE

PM4004



CLICK A FEATURE OR COMPONENT TO LEARN MORE



100%
Non
Metallic



Anti
Static



Large
Sizes
Available



Oil
Resistant



Protective
Midsole



Protective
Toecap



Small
Sizes
Available



Water
Repellent
Upper



Wide
Fitting



Highest Level
Slip Resistance



Upper Materials

Smooth Leather

Outsole

Activ-Step Dual Density

Internal Toecap

Composite

Lining Materials

Moisture wicking fabric

Footbed

EVA Footbed

Internal Midsole

Composite

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/01/2016

WWW.ROCKFALL.CO.UK | WWW.ROCKFALL.CO.UK/PRODUCTS/PM4004

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited
Unit 1 Major House
Wimsey Way
Alfreton, Derbyshire
England. DE55 4LS

E: sales@rockfall.co.uk
T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Declares that the PPE described hereafter;

PRO-MAN PM4004

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00331260** Issued by:-

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to

: Rock Fall UK Ltd
Major House, Unit 1 Wimsey Way, Alfreton, Derbyshire,
United Kingdom DE55 4LS

Authorised Representative

Manufacturer

Date of Issue

: 18 May 2013

Expiry Date

: 18 May 2018

Certificate No.


: LEC FI00331260

Product Reference(s)

: 4002/S3, 4003/S3, 4004/S3, 107 (TC310)/S3, 109B/S3,
109C/S3, 104/S3

Description

Construction	:	PU/PU Double Density Injection
Toecap	:	Steel Toecap
Midsole	:	Steel Plate
Last	:	604
Sole	:	PU/PU Injection
Mould	:	2010
Test Report(s)	:	See Technical File
Size Range	:	36 – 51
Category	:	S3 SRC


Assessor

18/05/2013

Date


Certification Manager

18/05/2013

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



TEST REPORT



Number: GZHT90166117

Tests Conducted (As Requested By The Applicant)

- 7 Internal Length Of Toe Cap (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.3)):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	42 mm	Min. 40 mm	Pass
	Right:	42 mm	Min. 40 mm	Pass

Expanded Uncertainty: 0.89 mm, with k= 2.22 at 95% confidence level

- 8 Impact Resistance (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.4)):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	16.0 mm	Min. 14.5 mm (#)	Pass
	Right:	16.0 mm	Min. 14.5 mm (#)	Pass

Remark: # =In Addition, The Toecap Shall Not Develop Any Cracks On The Test Axis Which Go Through The Material, ie. Through Which Light Can Be Seen.

Expanded Uncertainty: 0.49(Urel), with k= 1.96 at 95% confidence level

- 9 Compression Resistance (Toe Protection) BS EN ISO20344: 2004 /A1:2007(5.5):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	16.5 mm	Min. 14.5 mm	Pass
	Right:	17.0 mm	Min. 14.5 mm	Pass

Expanded Uncertainty: 0.13(Urel), with k= 1.96 at 95% confidence level

- 10 Outsole Slip Resistance (BS EN ISO 20344:2004/A1:2007 (5.18), SRC, 23 °C):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>			
	Heel Part	0.45	Min. 0.28	Pass
	Flat Contact	0.47	Min. 0.32	Pass
	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.17	Min. 0.13	Pass
	Flat Contact	0.20	Min. 0.18	Pass